


ALPHA PINENE OXIDE

ARKEMA
EPOXIDES

Structure



Description

Our Alpha Pinene Oxide is a specialty terpene.

Physical and Chemical Properties

CAS Number	1686-14-2
Viscosity (cps)	10
% Active	95
Acid Value	Less than or equal to 0.50
Vapor Density	5.24
Specific Gravity	0.964
Solubility in Water	Slight
Flash Point EF	144
Form	Liquid, w/ pine odor
Color	Clear, light yellow

Applications

Alpha Pinene Oxide is used in fragrance industry applications.

Packaging

Our terpene products are available in 5 gallon pails and 55 gallon drums. We can also provide custom packaging to fit your manufacturing requirements.

Custom Epoxidation and Outsourcing

We also provide custom epoxidation of terpenes and specialty alpha olefins, with outsourcing options for your

production needs. Our capabilities include manufacturing different optical rotations of terpenes.

Our experts in epoxidation technology welcome the opportunity to discuss your custom epoxidation requirements.

NOTE: Please consult the MSDS for updated and detailed safety and health information.

Environmental Safety Information

BEFORE HANDLING THIS MATERIAL, READ AND UNDERSTAND THE MSDS (MATERIAL SAFETY DATA SHEET) FOR ADDITIONAL INFORMATION ON PERSONAL PROTECTIVE EQUIPMENT AND FOR SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION.

For Environmental, Safety & Toxicology information, contact our Customer Service Department at (800) 446-2880 to request a Material Safety Data Sheet. ATOFINA Chemicals believes strongly in Responsible Care as a Public Commitment.

For Product and Technical Information Contact

Chuck Castley
Global Market Manager Epoxides
(856) 223-9829 (phone)
(856) 223-5492 (fax)
www.additives-arkema.com (website)
chuck.castley@arkemagroup.com (e-mail)

For Order Information Contact

Arkema Inc.
2000 Market Street, Philadelphia, PA 19103-3222
(800) 446-2800 (phone)
(215) 419-7875 (fax)
arkema.usph-additives-cs@arkemagroup.com (e-mail)

Visit us at our Website

www.additives-arkema.com

Vikoflex is a registered trademark of Arkema Inc.

Important Notice Regarding This Information

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein should be taken as an inducement to infringe any patent and the user is advised to take appropriate steps to be assured that and proposed use of the product will not result in patent infringement.

Note: The "Material Safety Data Sheet" on this product is available on request from the Safety and Environmental Services Department of Arkema Inc., 2000 Market Street, Philadelphia, PA 19103.



Arkema Inc.
2000 Market Street
Philadelphia, PA 19103
Customer Service 1.800.446.2800

www.additives-arkema.com