



TEGOGLAS (R) RP 40 LT

Material Safety Data Sheet

Arkema Inc.

1 PRODUCT AND COMPANY IDENTIFICATION

Functional Additives

2000 Market Street
21st Floor
Philadelphia, PA 19103-3222

EMERGENCY PHONE NUMBERS:

Chemtrec: (800) 424-9300 (24hrs) or (703) 527-3887
Medical: Rocky Mountain Poison Control Center
(866) 767-5089 (24Hrs)

Information Telephone Numbers	Phone Number	Available Hrs
Customer Service Number	(800) 331-7654	8:00 AM - 5:00 PM EST

Product Name TEGOGLAS (R) RP 40 LT
Product Synonym(s)

Chemical Family Polyethylene wax

Chemical Formula

Chemical Name

EPA Reg Num

Product Use Glass coating material

2 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS RegistryNumber	Typical %	OSHA
Polyethylene Wax Emulsion	Proprietary	>99	N

The substance(s) marked with a "Y" in the OSHA column, are identified as hazardous chemicals according to the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200)

This material is classified as hazardous under Federal OSHA regulation.

The components of this product are all on the TSCA Inventory list.

3 HAZARDS IDENTIFICATION

Emergency Overview

Beige liquid with a faint odor.

WARNING!

MAY CAUSE EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION.

Potential Health Effects

Inhalation and skin contact are expected to be the primary routes of occupational exposure to this material. Based on its composition, it is anticipated to be moderately irritating to eyes and skin. Repeated exposure may cause an allergic skin reaction.

4 FIRST AID MEASURES

IN CASE OF CONTACT, flush the area with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops and persists.

4 FIRST AID MEASURES

IF INHALED, remove to fresh air.

IF SWALLOWED, do NOT induce vomiting. Give water to drink. Get medical attention immediately. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

5 FIRE FIGHTING MEASURES**Fire and Explosive Properties**

Auto-Ignition Temperature	NE	
Flash Point	NE	Flash Point Method
Flammable Limits- Upper	NE	
Lower	NE	

Extinguishing Media

Use water spray, carbon dioxide, foam or dry chemical.

Fire Fighting Instructions

Contain run-off from fire. Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

Fire and Explosion Hazards

When burned, the following hazardous products of combustion can occur:
Oxides of carbon

6 ACCIDENTAL RELEASE MEASURES**In Case of Spill or Leak**

Isolate hazard area and deny entry to unnecessary or unprotected personnel. Contain spilled liquid with sand or earth. Clean up spill immediately, observing precautions in the Personal Protection section of MSDS. Avoid runoff into storm sewers and ditches which lead to waterways.

7 HANDLING AND STORAGE**Handling**

Avoid contact with eyes, skin and clothing. Do not taste or swallow.

Keep container closed.

Emptied container retains vapor and product residue. Observe all labeled safeguards until container is cleaned, reconditioned or destroyed.

Storage

Keep from freezing; material may separate.

This material is not hazardous under normal storage conditions; however, material should be stored in closed containers, in a secure area to prevent container damage and subsequent spillage.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Engineering Controls**

Investigate engineering techniques to reduce exposures. Provide ventilation if necessary to minimize exposures. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Eye / Face Protection

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment available.

Skin Protection

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Wear face shield and chemical resistant clothing such as a rubber apron when splashing may occur. Rinse contaminated skin promptly. Wash contaminated clothing and clean protective equipment before reuse. Wash skin thoroughly after handling.

Respiratory Protection

Where airborne exposure is likely, use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. If exposures cannot be kept at a minimum with engineering controls, consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Airborne Exposure Guidelines for Ingredients

The components of this product have no established Airborne Exposure Guidelines

- Only those components with exposure limits are printed in this section.
- Skin contact limits designated with a "Y" above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required.
- ACGIH Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic reactions.
- WEEL-AIHA Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic skin reactions.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor	Beige liquid with a faint odor.
pH	9.0
Specific Gravity	1.0
Vapor Pressure	NE
Vapor Density	More than air
Melting Point	NA
Freezing Point	NE
Boiling Point	212-221 F
Solubility In Water	Soluble

10 STABILITY AND REACTIVITY

Stability

This material is chemically stable under normal and anticipated storage and handling conditions.

Hazardous Polymerization

Does not occur.

Incompatibility

None known

Hazardous Decomposition Products

None known

11 TOXICOLOGICAL INFORMATION

Toxicological Information

Data on this material and/or its components are summarized below.

Polyethylene wax emulsion

Single exposure (acute) studies indicate that this material is moderately irritating to rabbit skin and severely irritating to eyes.

An allergic skin reaction may occur following repeated skin exposure. Inflammatory changes in the lungs of rabbits was observed in skin tests with a similar material.

12 ECOLOGICAL INFORMATION

Ecotoxicological Information

Data on this material and/or its components are summarized below.

Polyethylene wax emulsion

This material is moderately toxic to *Daphnia magna* (48-hr LC50 1.5-1.7 mg/l) and fathead minnow (96-hr LC50 3.1-3.8 mg/l). It is practically non-toxic to bacteria (LC50 >2,500 mg/l).

Chemical Fate Information

No data are available.

13 DISPOSAL CONSIDERATIONS

Waste Disposal

Incineration is the recommended method for disposal observing all local, state and federal regulations.



14 TRANSPORT INFORMATION

DOT Name Not regulated
DOT Technical Name
DOT Hazard Class
UN Number
DOT Packing Group PG
RQ

15 REGULATORY INFORMATION

Hazard Categories Under Criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	Y	Fire	N
Delayed (Chronic) Health	N	Reactive	N
		Sudden Release of Pressure	N

The components of this product are all on the TSCA Inventory list.

Ingredient Related Regulatory Information:

SARA Reportable Quantities	CERCLA RQ	SARA TPQ
Polyethylene Wax Emulsion	NE	

16 OTHER INFORMATION

Revision Information

Revision Date 02 JAN 2007 Revision Number 6
Supersedes Revision Dated 19-OCT-2004

Revision Summary

The name of this business group has changed to Functional Additives.

Key

NE= Not Established NA= Not Applicable (R) = Registered Trademark

The specific identity of the polyethylene wax emulsion is withheld because it is trade secret information of Arkema Inc.

Arkema Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Arkema Inc., Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.