



ORGANIC PEROXIDE SPILL CLEAN UP

Organic peroxide spills should be attended to **immediately** via the following procedures:

- Spills can normally be handled by spreading an inert absorbent material such as sodium bicarbonate, sawdust, vermiculite or sand directly on the spill, then wetting down (dampen) the mixture with water. The mixture of the spilled peroxide and the inert absorbent material should be swept up using non-sparking tools and placed in a polyethylene bag for disposal. **NOTE:** A supply of suitable inert absorbent material should be kept available for this purpose in areas where organic peroxides are used.
 - The sweepings in the polyethylene bag should be wetted down further, with water, and disposed of **immediately** by an approved disposal company. Disposal must comply with federal, state and local regulations. Refer to the Arkema Organic Peroxide Disposal bulletin for additional information.
 - If stored for any period of time, the sweepings should be out of direct sunlight in a cool, well-ventilated place.
- After all the material has been picked up, wash down the area with surfactant and water to remove any trace amounts of organic peroxide. Allow for sufficient ventilation to aid in the removal of fumes that may be present.

As in all cases where safety issues are involved, contact Arkema Inc. if you have any questions.

Arkema Inc. is dedicated to Responsible Care[®] and Product Stewardship[®].

In Case of Emergency Call: CHEMTREC (800)-424-9300 24 Hours / Day

**In Case of Medical Emergency Call:
Rocky Mt. Poison Control Center (303) 623-5716 24 Hours / Day**

Arkema Inc. Organic Peroxide Hotline: (800)-558-5575

**Arkema Inc. • Organic Peroxides • www.luperox.com
2000 Market Street, Philadelphia, Pa. 19103
Phones: (800) 558-5575 • Fax: (215) 419-7413 • 24 Hr. Emergency No. (800) 424-9300**

© 2007 Arkema Inc. All rights reserved.

® Product Stewardship & Responsible Care are registered trademarks of the American Chemistry Council.

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein should be taken as an inducement to infringe any patent and the user is advised to take appropriate steps to be assured that any proposed use of the product will not result in patent infringement. .

(Revision #3, 03/15/07)