



ARKEMA INC.
2000 Market Street
Philadelphia, PA 19103
215-419-7000
www.e-organicchemicals.com

SPOTLEAK 1410

SPECIFICATIONS

Appearance	Clear Liquid
Color Apha	≤35
Cloud Point °F	≤-50° (-45.5°C)
Composition (GC) wt %	
T-Butyl Mercaptan	49.0-51.0
Dimethyl Sulfide	49.0-51.0

The above specifications are determined according to Arkema Inc. Analytical Methods.

PROPERTIES

Specific Gravity @15.5/15.5 °C	0.828
Average wt. Pounds per Gallon @ 15.5°C (60 °F)	6.90
Flash Point, TCC °F	< 0°F
Vapor Pressure @ 100 °F, psia	10.8
Coefficient of cubical expansion per °C	0.0013 (0.00072/°F)

Customer Service: 1.800.628.4453

May 15, 2007

BEFORE HANDLING THIS MATERIAL, READ AND UNDERSTAND THE MSDS (MATERIAL SAFETY DATA SHEET) FOR ADDITIONAL INFORMATION ON PERSONAL PROTECTIVE EQUIPMENT AND FOR SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein should be taken as an inducement to infringe any patent and the user is advised to take appropriate steps to be assured that any proposed use of the product will not result in patent infringement.