

FASCAT[®] 4224 CATALYST

PRODUCT INFORMATION

DESCRIPTION

Arkema Inc. FASCAT 4224 catalyst is a viscous amber liquid with the following properties:



TYPICAL PROPERTIES

% Sn	26.4
Molecular Weight	447
Boiling Point (°F)	> 200
Melting Point (°F)	-7
Solubility	Insoluble in water. Highly soluble in esters, alcohols and hydrocarbons.

PRODUCT FEATURES

FASCAT 4224 catalyst is an organotin thioglycerol catalyst designed for use in systems where some hydrolytic stability is required.

FASCAT 4224 catalyst is a hydrolytically stable and dispersible liquid catalyst in waterborne applications.

RECOMMENDED USES

FASCAT 4224 catalyst is used for silicone caulk and sealant applications.

FASCAT 4224 catalyst is used for waterborne urethane coating applications.

PACKAGING

FASCAT 4224 catalyst is available in 10 lb and 55 lb (25 kg) pails.

Arkema Inc.

2000 Market Street
Philadelphia, PA 19103-3222
(800) 331-7654
Fax: (215) 419 7064

Arkema

Additives Division
4-8 Cours Michelet – La Defense 10
F-92091 Paris la Defense Cex
Phone: (33) 01 49 00 80 80
Fax: (33) 01 49 00 88 40

Arkema Pte Ltd

10 Science Park Road #01-01A
The Alpha Singapore Science Park II
Singapore 117684
Phone: +65 6419 9199
Fax: +65 6419 9188

Email: info.additives@arkema.com





The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

See MSDS for Health & Safety Considerations
© 2006 Arkema Inc. All rights reserved.



Arkema Inc
2000 Market Street
Philadelphia, PA 19103
215-419-7000
www.arkema.com